

HAKI Safety



Slab edge with multiple clamps, standards and safety gates with net



Multiple clamp

7155141 (8.1 kg)

The multiple clamp can be fitted both horizontally and vertically as a holder for the standard. It has a self-cleaning, rugged thread and is designed for material of thickness 70 – 370 mm. The multiple clamp is used on edges of slabs, tops of walls or similar, and on all types of material.



Top of wall with multiple clamps, standards and guardrail frame

HAKI Safety is a further way of using HAKI's basic components.

With the help of a couple of new components, you can fit temporary personal fall protection devices onto slab edges and suchlike. The standard FSSH 1000 is fitted to a clamp and used as a guardrail post. The guard consists of a safety gate with net SGF or a guardrail frame SKRD combined with a toeboard.

Some simple accessories that make it possible to utilize HAKI's scaffolding system even better

– as the **HAKI Safety fall protection system**.

HAKI Safety



Slab with screw base joints, standards, guardrail frames and toeboards

Screw base joint

7155140 (1.6 kg)

The screw base joint is a simple fixing for floor slabs and other horizontal surfaces of concrete, steel or wood. The M16 screw of the base joint is installed in an embedded dowel or similar. The screw is easy to replace.



The gate bracket SGF allows you to place guardrail posts where you want when using safety gates with net

If the distance or the angle between a couple of guardrail posts does not suit the modular size of the rails, a gate bracket is used for SGF or a guardrail bracket for SKRD. The brackets make it possible to place the next standard at any distance or in any direction.

Gate bracket SGF

7053108 (4.3 kg)

Guardrail bracket SKRD

7053109 (1.8 kg)



The guardrail bracket SKRD allows you to place guardrail posts where you want when using guardrail frames



HAKI AB

SE-280 63 Sibbhult, Sweden

Tel +46 44 494 00 Fax +46 44 494 72

info@haki.se www.HAKI.com